



**MACRO TO WIDE ANGLE LENS 1 MWL-1**  
FOR FULL FRAME 60MM EQUIVALENT LENSES TO 150° ULTRA WIDE WET-MOUNTED

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
N120 CANON EF-MOUNT	MACRO FULL FRAME	Canon EF 40mm f/2.8 STM <i>* This setup can only be used on APS-C sensor camera</i>			18706 Macro Port 12	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	On APS-C Sensor Lens FOV Converted FOV 37° 135°	
	STANDARD ZOOM FULL FRAME	Canon EF 28-80mm f/3.5-5.6 II	19558 C2880F3.SII-Z	21110 N120 Extension Ring 10	18705 Macro Port 45 <i>* This setup is only compatible with 18705 before SN:A364081</i>	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 36-30° 135-113° 66-80mm	
				22110 N120 Extension Ring 10 II	18705 Macro Port 45 <i>* This setup is only compatible with 18705 SN:A364081 onwards</i>				
	STANDARD ZOOM FULL FRAME	Canon EF 28-80mm f/3.5-5.6 V USM	19559 C2880F3.SV-Z	21110 N120 Extension Ring 10	18705 Macro Port 45 <i>* This setup is only compatible with 18705 before SN:A364081</i>	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 37.5-30° 138-93° 63-80mm	
22110 N120 Extension Ring 10 II				18705 Macro Port 45 <i>* This setup is only compatible with 18705 SN:A364081 onwards</i>					
N120 CANON RF-MOUNT	WIDE ANGLE FULL FRAME	Canon RF 35mm f/1.8 IS Macro STM <i>* These setups are only recommended to use for blackwater photography with slight vignetting on 1.6x (crop) for still photography and with movie cropping option enabled</i>		21110 N120 Extension Ring 10	18706 N120 Macro Port 12 <i>* This setup is only compatible with 18706 before SN:A524910</i>	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 42° 157.5°	
				22110 N120 Extension Ring 10 II	18706 Macro Port 12 <i>* This setup is only compatible with 18706 SN:A524910 onwards</i>				
N100 CANON RF-MOUNT	STANDARD ZOOM APS-C	Canon RF-S 18-45mm f/4.5-6.3 IS STM	19596 CRS1845-Z		37181 N100 Flat Port 50	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 40-35° 150-130° 38-45mm	
N100 NIKON Z-MOUNT	MACRO APS-C	NIKKOR Z MC 50mm f/2.8 Macro		37430 N100 Extension Ring 30 II	37601 N100 Flat Port 29	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 31.5° 119°	
					37124 Flat port 66 with M77 Thread				83251 M77 to Bayonet Mount Converter II
N100 SONY E-MOUNT	MACRO FULL FRAME	Sony SEL50M18 FE 50mm f/1.8			37123 N100 Macro Port 55 <i>* These setups are only recommended to use with Crop/APS-C format enabled to avoid vignetting</i>	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 31° 116°	
					37141 SE2870-Z				37430 N100 Extension Ring 30 II
N85 MICRO FOUR THIRDS SYSTEM	MACRO FOUR THIRDS	Olympus M.Zuiko Digital ED 30mm f/3.5 Macro			36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 39° 150°	
		Panasonic Lumix G Macro 30mm f/2.8 Asph. Mega O.I.S.			36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 39° 150°	
	STANDARD ZOOM FOUR THIRDS	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 &amp; NA-EM1X</i>		37430 N100 Extension Ring 30 II	36161 N85 Macro Port with M77 Thread <i>* 36167 Gear Set for NA-OM1</i>	83251 M77 to Bayonet Mount Converter II	86201 MWL -1	Lens FOV Converted FOV Zoom Range 39-34° 150-71° 30-50mm
N85 SONY E-MOUNT	MACRO APS-C	ZEISS Touit 50mm f/2.8M Macro			36630 N85 Extension Ring 30	36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV 31° 116°
					36174 SE1670-Z				
SONY	STANDARD ZOOM APS-C	Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package)				83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 37-34° 138-128° 65-70mm	
		* 24-70mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>							
		Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package)				38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		86201 MWL -1	Lens FOV Converted FOV Zoom Range 40-37° 150-138° 60-65mm
	* 24-200mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>								
	Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package)				38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		86201 MWL -1	Lens FOV Converted FOV Zoom Range 37° 138° 65mm	
	* 24-200mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>								
N50 & COMPACT	CANON	Canon Powershot G7XMKII (17324 NA-G7XII)				83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 37-24° 138-90° 65-100mm	
		* 24-100mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>							
		Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package)				38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		86201 MWL -1	Lens FOV Converted FOV Zoom Range 37-24° 138-90° 65-100mm
	* 24-100mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>								
	Canon EOS R50 with RF-S 18-45 F4.5-6.3 IS STM Lens (17340/17340P NA-R50 / Pro Package)						86201 MWL -1	Lens FOV Converted FOV Zoom Range 40-35° 150-130° 38-45mm	
	* 24-100mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>								
PANASONIC	STANDARD ZOOM APS-C	Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10)				83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL -1	Lens FOV Converted FOV Zoom Range 37-34° 138-128° 65-72mm	
	* 24-72mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>								

**86201**  
**MACRO TO WIDE ANGLE LENS 1 (MWL-1)**  
For Full Frame 60mm Equivalent macro lenses to 150° ultra wide wet-mounted

**Specifications**

Dimension (mm)	:	DIA 108 x H 120 (from port mount to front lens element)
Weight in Air	:	1.20 kg
Buoyancy in Water	:	Negative 0.58 kg
Body Construction	:	Hard-anodized aluminum alloy
Lens Construction	:	7 Elements in 5 Groups
Lens Coating	:	Anti-corrosion coating outside of dome Anti-reflection coating on other surfaces
Focus Distance	:	From front element of lens to infinity
Maximum FOV (underwater)	:	150° (Ref. 60mm equivalent)
Lens Mount	:	Bayonet/M67
Depth Rating	:	100m
Pre-installed	:	Integrated aluminium float collar

**Package includes**

- MWL-1
- Front hard lens cap
- Rear lens caps
- Bayonet Mounting Ring
- Cleaning Cloth
- Padded carrying bag